



RUGGED DURABILITY FOR YOUR CREATIVE LIFE AND ADVENTURES


The **G-DRIVE® ArmorATD™** rugged portable hard drive is designed to protect your content anywhere. Through every adventure and creative journey, this durable drive provides creator-ready reliability and peace-of-mind for all creators.

- Premium, anodized aluminum enclosure for strength you can feel
- Built tough with an easy-grip bumper for pro-grade durability you can trust
- Rain, dust, and crush resistant enclosure†
- Up to 6TB* of reliable storage and backup of critical photos, videos and files
- Transfer rates of up to 130MB/s read**
- USB-C™-ready (5Gbps) and Thunderbolt™ 3 compatible
- 3 year limited warranty







G-DRIVE® ArmorATD™




Up to 1000 lbs
Crush Resistance



Shock
Resistance***



USB
5Gbps



3 Year Limited
Warranty



SPECIFICATIONS

Interface	USB Type-C™
Drive	2.5" hard drive
Data Transfer Rate	Up to 130MB/s read**
Operating Temperature	41°-95° F (5°-35°C)
Size (LxWxH)	6TB, 5TB, 4TB: 5.24 x 3.50 x 1.26 in / 133.0 x 89.0 x 32.0 mm 2TB, 1TB: 5.12 x 3.43 x 0.93 in / 130.0 x 87.0 x 24.0 mm
Weight	6TB, 5TB, 4TB: 0.84 lb / 0.38 kg 2TB, 1TB: 0.56 lbs / 0.25 kg
Operating Systems	macOS 11+ (Time Machine compatible) Windows® 10+ (Via Reformat)
Box Contents	G-DRIVE ArmorATD USB-C to USB-C Cable USB-C to USB-A Cable Quick Start Guide
Retail Packaging	(LxWxH): 1.9 x 4.7 x 7.2 in / 48 x 120 x 183 mm

WORLDWIDE

Capacity*	SKU	UPC	EAN
6TB	SDPHE1G-006T-GBAND	7 18037 90363 7	0 718037 903637
5TB	SDPH81G-005T-GBA1D	7 18037 90268 5	0 718037 902685
4TB	SDPH81G-004T-GBA1D	7 18037 90266 1	0 718037 902661
2TB	SDPH81G-002T-GBA1D	7 18037 90264 7	0 718037 902647
1TB	SDPH81G-001T-GBA1D	7 18037 90262 3	0 718037 902623

CHINA

Capacity*	SKU	UPC	EAN
6TB	SDPHE1G-006T-ZBAND	7 18037 90364 4	0 718037 903644
5TB	SDPH81G-005T-ZBA1D	7 18037 90269 2	0 718037 902692
4TB	SDPH81G-004T-ZBA1D	7 18037 90267 8	0 718037 902678
2TB	SDPH81G-002T-ZBA1D	7 18037 90265 4	0 718037 902654
1TB	SDPH81G-001T-ZBA1D	7 18037 90263 0	0 718037 902630

* 1TB = 1 trillion bytes. Actual user capacity may be less depending on operating environment.

** 1 MB/s = 1 million bytes per second. Based on internal testing; performance may vary depending upon host device, usage conditions, drive capacity, and other factors.

*** Shock resistance up to 1.2m on a carpeted concrete floor for 1TB and 2TB capacities, and up to 1m on a carpeted concrete floor for 4TB, 5TB and 6TB capacities.

† IEC 60529 IP54; Based on internal testing. Tested to withstand water splashing against the enclosure; limited dust contact does not interfere with operation. Must be clean and dry before use.

Western Digital, the Western Digital design, the Western Digital logo, G-DRIVE, the G Logo and ArmorATD are registered trademarks or trademarks of Western Digital Corporation or its affiliates in the US and/or other countries. USB-C is a trademark of USB Implementers Forum, Inc. macOS, Mac and Time Machine are trademarks of Apple Inc. Windows is a trademark or registered trademark of Microsoft Corporation in the US and/or other countries. Thunderbolt is a trademark of Intel Corporation or its subsidiaries. All other marks are the property of their respective owners.

Product specifications subject to change without notice. Pictures shown may vary from actual products.

© 2025 Western Digital Corporation or its affiliates. All rights reserved.

