

Samsung Portable SSD

T9

2023 Data Sheet

Revision 1.0



DISCLAIMER

SAMSUNG ELECTRONICS RESERVES THE RIGHT TO CHANGE PRODUCTS, INFORMATION AND SPECIFICATIONS WITHOUT NOTICE.

Products and specifications discussed herein are for reference purposes only. All information discussed herein may change without notice and is provided on an "AS IS" basis, without warranties of any kind. This document and all information discussed herein remain the sole and exclusive property of Samsung Electronics. No license of any patent, copyright, mask work, trademark or any other intellectual property right is granted by one party to the other party under this document, by implication, estoppels or otherwise. Samsung products are not intended for use in life support, critical care, medical, safety equipment, or similar applications where product failure could result in loss of life or personal or physical harm, or any military or defense application, or any governmental procurement to which special terms or provisions may apply. For updates or additional information about Samsung products, contact your nearest Samsung office (www.samsung.com/samsungssd and www.samsung.com/support). All brand names, trademarks and registered trademarks belong to their respective owners.

COPYRIGHT © 2023

This material is copyrighted by Samsung Electronics. Any unauthorized reproductions, use or disclosure of this material, or any part thereof, is strictly prohibited and is a violation under copyright law.

Technical Specifications

Samsung Portable SSD T9				
Interface	USB 3.2 Gen 2x2 (20Gbps)			
Hardware Information	Capacity ¹	1TB	2TB	4TB
	Dimensions	88 x 60 x 14mm		
	Weight	122 grams ²		
Performance	Sequential Read ³	Up to 2,000 MB/sec	Up to 2,000 MB/sec	Up to 2,000 MB/sec
	Sequential Write ³	Up to 1,950 MB/sec	Up to 1,950 MB/sec	Up to 2,000 MB/sec
Durability	Drop Resistant	Up to 3m ⁴		
Security	Encryption	AES 256-bit hardware encryption		
	Software	Samsung Portable SSD 1.0 ⁵ Samsung Magician Software		
Reliability	Temperature	Operating	0°C to 60°C ⁶	
		Non-Operating	-40°C to 85°C	
	Humidity		5% to 95% non-condensing	
	Shock	Non-Operating	1,500G, duration: 0.5ms, 3 axis	
	Vibration	Non-Operating	20~2,000Hz, 20G	
Certifications		CE, BSMI, KC, VCCI, RCM, FCC, IC, UL, TUV, CB, EAC, UKCA, BIS		
RoHS Compliance		RoHS 2		
Warranty ⁷	Period	Five (5) Year Limited Warranty		

1. 1 GB=1,000,000,000 bytes, 1 TB=1,000,000,000,000 bytes. Lower capacity may be demonstrated by your computer due to use of a different measurement standard.

2. Exact weight of product may vary by capacity.

3. Max data transfer speed is measured based on Samsung's internal testing standards with the enclosed cable. Performance may vary depending on host configuration, cable and user system environment.

4. The drop test was conducted under controlled conditions. Drop resistance may vary depending on the actual environmental conditions. Damage caused by drop is not covered under warranty.

* Test condition: Device was dropped free-fall to a metal plate from 3-meter height.

** No warranty is provided for any physical damage.

5. T9 Software's minimum System Requirements: Windows 7 or higher, Mac OS X 10.10 or higher, Android Lollipop or higher

6. Tc is measured at the hottest point on the case. Sufficient airflow is recommended to be operated properly on heavier workload within device operating temperature.

7. Please refer to the detailed warranty statement here at <https://semiconductor.samsung.com/consumer-storage/support/documents/>. The LED component of the T9 is warranted for five (5) years of typical use, typical use for the purposes of this warranty defined as four (4) hours of operation per day at temperatures of 40°C or below.

SAMSUNG

PRODUCT LINE-UP

Density	Model Name	Model Code	Box Contents
4TB	MU-PG4T0	MU-PG4T0B/WW	<ul style="list-style-type: none"> • Samsung Portable SSD T9 • USB Type-C to A cable • USB Type-C to C cable • Quick User Manual & Warranty Statement
		MU-PG4T0B/AM	
		MU-PG4T0B/EU	
2TB	MU-PG2T0	MU-PG2T0B/WW	
		MU-PG2T0B/AM	
		MU-PG2T0B/EU	
1TB	MU-PG1T0	MU-PG1T0B/WW	
		MU-PG1T0B/AM	
		MU-PG1T0B/EU	